

REFERENCES

REFERENCIAS

FABRICANTE: TYCO

MANUFACTURER

FABRICANTE

TENSAO DE TRABALHO: 24V

VOLTAGE

VOLTAJE

CARROCERIA: INDIFERENTE

BUS BODY / COACH BODY

CARROCERIA

TIPO: ELETROMAGNETICA

TYPE

TIPO

CHASSI: INDIFERENTE

CHASSIS

CHASIS

Specification:

- Rated voltage 12Vdc/24Vdc

- Maximum switching voltage 16Vdc/32Vdc

- Limiting continuous current- **load current from terminal B(+) to A(-)**

23°C, load cable 50mm2 260A

85°C, load cable 50mm2 190A

125°C, load cable 50mm2 88A

- Limiting making current, resistive load, cable 50mm2, 23°C, ton/toff=0.5s/10min - 1500A, >5 ops.

- Limiting breaking current, resistive load, cable 50mm2, 23°C, ton/toff=0.5s/10min - 1500A, >5 ops.

- Limiting short-time current, overload current at 23°C, cable 50mm2, 1000A, 1s - 0A, 9s - 50x103 ops.

- Protection IP54.

- Weight approx. 210g

ITEM	CODE	QTY
------	------	-----

 Marcopolo Project Office: ENO_MPIO Reviser by SAP WorkFlow VIEW IN PLM SYSTEM Drawer DEHIRISI Use:	Denomination: CHAVE GERAL MAIN SWITCH LLAVE GENERAL	Code: 10466375 Class: 152006
--	--	---