






Number	Date	Modification	E	Owner
500000031602	01/09/2009			F66094
500000094792	04/05/2012	ALTERADO CONFORME SPE I76098		F66R50




NITRETAR CAMADA: 0,20MM  
DUREZA 55HRC




CEMENTAR/PROF.: 0,50 +/-0,10MM  
TEMPERAR/REVENIR: 650 A 700 HV




NITRETAR CAMADA: 0,20MM  
DUREZA 55HRC




NITRETAR CAMADA: 0,20MM  
DUREZA 55HRC







CEMENTAR/PROF.: 0,30 +/-0,10MM  
TEMPERAR/REVENIR: 650 A 700 HV



CEMENTAR/PROF.: 0,50 +/-0,10MM  
TEMPERAR/REVENIR: 650 A 700 HV



NITRETAR CAMADA: 0,20MM  
DUREZA 55HRC



Dimensões	01-3	3-6	6-10	10-15	15-20	20-30	30-40	40-50	50-60	60-80	80-100	100-150	150-200	200-400
Comprimento	+0,1	+0,1	+0,2	+0,3	+0,4	+0,5	+0,6	+0,8	+1,0	+1,2	+1,5	+2,0	+2,5	+3,0
Diâmetro	+0,03	+0,04	+0,05	+0,06	+0,08	+0,10	+0,12	+0,15	+0,20	+0,25	+0,30	+0,40	+0,50	+0,60
Acabamento	1	2	3	4	5	6	7	8	9	10	11	12	13	14

POSICAO DA CHAVE: NENHUM  
KEY POSITIONING: POSITION SE LLAVE  
SISTEMA DE ABERTURA: CHAVE BOTAO  
CHINA/SISTEM: SISTEMA DE ABERTURA  
SISTEMA DE FIXACAO: PARAF./REBITADA  
ATTACHMENT SYSTEM: SISTEMA DE FIXACAO  
LADO: ESQUERDO  
SIDE: L-DO  
TRATAMENTO SUPERFICIAL: FE/ZN 12c2  
SURFACE TREATMENT: TRATAMIENTO SUPERFICIAL  
SEGredo FECHADURA: 0  
LOCK HERE: SEGredo FECHADURA  
TIPO CHAVE: SEM CHAVE  
KEY TYPE: TIPO LLAVE

ITEM	CODE	QTY
------	------	-----

Scale: 1:1 Date: 4/5/2012  
 Liquid weight: 0,620  
 Origin: 1014/711  
 Version:  
**AC**  
 Drawn: Revisor: Approved:

**FECHOS E FECHADURAS**  
 LOCKS AND LATCHES  
 CIERRES Y CERRADURAS  
**FECHADURA PROTEGIDA PARA PORTINHOLA TRASEIRA**  
 Code: **10141713**  
 Class: 990901